

978 Hermitage Road NE • Rome GA 30161  
800-328-9203 • 706-295-4111 Fax: 706-295-4114

Email: info@jchinternational  
Web: www.jchinternational.com

## **Champion Sports Flex Maintenance**

### **IMPORTANT INFORMATION FOR THE SPECIFIER**

#### **JCH International recommends the Taski-Sutter Cleaning and Maintenance Program For Champion Sports Flex**

Proper protection and maintenance of **Champion Sports Flex** post-installation should be specified by the architect/designer. **Champion Sports Flex** products are not precoated with a factory finish; therefore, they should not be subject to debris and potential damage caused from heavy duty construction activities.

#### FLOOR PROTECTION

The specifier should include specification details to protect the floor post-installation and until job construction is complete, such as covering the entire floor with paper or other floor covering device (plastic, plywood, etc.) until construction is final and thorough cleaning and maintenance can begin.

#### ASSIGNMENT OF CLEANING AND MAINTENANCE

The specifier should determine and assign the responsibility for the final cleaning and finishing. This responsibility should be specifically assigned to either the flooring contractor, general contractor, maintenance contractor or owner.

### **TASKI SUTTER CLEANING AND MAINTENANCE PROGRAM FOR JCH INTERNATIONAL**

#### **1. Outdoor Cleaning & Maintenance Procedures**

- a. Daily cleaning- Sweep debris away or hose off dirt.
- b. Periodic cleaning (as needed)- Pressure wash with no more than 1200 psi maximum.

#### **2. Indoor Cleaning & Maintenance Procedures**

- a. Daily cleaning- Vacuum or sweep floor to remove loose debris
- b. Wet scrub floor with Taski profi cleaner (6-8 oz per gallon of water), using buffer or auto scrubber with Taski contact pad or nylon brush.
- c. Wet vacuum remaining soiled solution, rinse and allow to dry thoroughly (6-8 hours).
- d. Apply 2-3 coats of 50/50 (wiwax & water) solution.

## I. CLEANING & MAINTENANCE PROCEDURES

### **Important tips for Rubber Floors:**

- Use high CFM vacuum to pick up dust
- Wait for floor to dry before applying coats of floor finishes.
- Apply floor finishes (thin coats) with finish mop.
- For large areas, use auto scrubbers to clean floors.
- For stripping floors, use TASKI ice-it and nylon brush. For poorly maintained floors, you may be required to continue cleaning with ice-it for an extended period.
- For food areas, use TASKI profi (2-4 oz/gal. of water).
- For gum, use any generic gum remover, however, any solvent based product should be rinsed well with water to avoid damaging floor.
- For high traffic areas, top scrub and recoat floor as needed.

### **A. Post installation**

1. Sweep floor clean. Dry vacuum to ensure any fine soil is removed.
2. Wet scrub floor with TASKI profi cleaner (6-8 oz/gal of water), using buffer or auto scrubber with TASKI contact pad or soft nylon brush.
3. Wet vacuum remaining soiled solution, rinse and allow to dry thoroughly (6-8 hours).

### **B. Daily cleaning**

1. Dry vacuum floor thoroughly.
2. Auto scrub or wet mop floor using TASKI profi cleaner (4 oz/gal of water) or wiwax cleaner/maintainer (2 oz/gal of water). *Note: Profi is not a stripper. There is no need to refinish after cleaning with TASKI profi.*

### **C. Periodic cleaning (as needed)**

1. Dry vacuum floor thoroughly.
2. Wet scrub floor with TASKI profi (4 oz/gal of water) or wiwax (2 oz/gal of water). This cleaning may be performed with an auto scrubber, buffer and wet vacuum or wet mop. *Note: Profi is not a stripper. There is no need to refinish after cleaning with TASKI profi.*
3. Scrub wet floor with scrubbing pad (TASKI purple pad).
4. Vacuum soiled solution with a wet/dry vacuum.
5. Allow floor to dry.
6. Apply 1-2 coats of finish as indicated under II Finish Options.

## II. FINISH OPTIONS

- A. **TASKI vision matte™** – FOR A LOW SATIN FINISH. TASKI vision matte requires little maintenance and promotes a low matte shine.
  - Apply 2-3 thin coats of finish allowing a minimum of 30 minutes dry time between coats.
  
- B. **TASKI vision star™** – FOR A HIGH GLOSS SHINE TASKI vision star provides a high gloss finish with extra durability.
  - Apply 2-3 thin coats of finish allowing a minimum of 30 minutes dry time between coats.
  
- C. **TASKI wiwax™** – FOR A COMBINED DETERGENT/MAINTAINER WITH A SATIN SHINE FINISH. TASKI wiwax cleans and leaves a protective thin film, preventing soils from penetrating the floor.
  - Apply 2-3 coats of a 50/50 (wiwax & water) solution.