

978 Hermitage Road NE • Rome GA 30161
800-328-9203 • 706-295-4111 Fax: 706-295-4114

Email: info@jchinternational.com
Web: www.jchinternational.com

Specifications:

Manufacturing Method: Fiber V-loop double needlepunch

Surface: Polypropylene - Solution dyed olefin fibers

Backing: Vinyl drainage knobs

Properties:

- Colorfastness: all colors show a rating of not less than "good" after exposure to 500 Standard Fading Hours, testing as specified in Method 5660 of FTMS CCC-T-1916
- Abrasion Resistance: Wear index in excess of 12,000 revolutions, Taber Abrader, H-10 wheels, with weights of 1000 grams per wheel
- Acoustical properties: Noise reduction coefficient rating NRC .25-.35 when tested per ASTM C423-68.
- Flammability: Products shall pass the requirements of DOC FF 1-70, 2-70, and ASTM E648, along with ASTM R662 smoke generation
- Miscellaneous: Resistant to Carpet Beetles, Vermin (per ASTM D-1116-65T) and Fungus (FTMS Method 5762)

Maintenance:

- Use powerful industrial vacuum with beater or brush action for best results
- Clean via any commercially accepted carpet cleaning method, such as steam cleaning, hosing down, or wet cleaning
- Most solvents may be used to remove spots of oil, paint, etc. Diluted chlorine bleach has no adverse effect on colors.
- Caution: When using industrial strength solvents/detergents, apply to the rag only (not directly to the carpet). Make sure the solvents are not allowed to soak into the rubber backing, as it will destroy it.

Installation:

Install over clean, dry, firm, smooth, even surfaces, free of cracks, foreign substances, oil, or loose paint. It is recommended to glue down this carpet with the recommended adhesive when it is subjected to heavy commercial use. Product may be loose laid.

Size and Weights:

Face Fiber:	Blend of 18-240 dpf solution dyed UV stabilized olefin fiber
Face fiber Weight (approx):	1100 gm/m ² (32 ozs/sy)
Primary Backing- Latex (approx):	200 gm/m ² (6 ozs/sy)
Backing- Natural/Synthetic Rubber:	100 gm/m ² (3 ozs/sy)
Total Weight (approx):	1400 gm/m ² (42 ozs/sy)
Roll Length (approx):	21m (70 lin ft)
Width:	78" and 39"

Product subject to commercial shade match variations

Limited Warranty:

Limited Three (3) Year General or One (1) Year Sunbelt Fade Warranty

JCH International warrants that the face fiber in the above product will not disintegrate for a period of Three (3) Years under normal conditions in commercial outdoor use due to the ultra-violet degradation, to the point where the backing is exposed. There may be some shade variation due to UV exposure, but such shade variation is not subject to this warranty. This is for a period of One (1) Year on commercial outdoor installations in Sun Belt States (AZ, FL, NM, TX, and the Southern halves of CA, CO, and UT). In the event of a warranty claim established to JCH International's satisfaction, JCH International will assume the cost of replacement product on a depreciating basis based on the replacement cost of the product: First Year- 100%, Second Year- 50%, Third Year- 25%. Proof of installation date must be registered with JCH International, or its representative, as stipulated below.

Limited Five (5) Year Commercial Abrasive Wear Warranty

JCH International warrants commercial glue-down indoor installations (made with JCH's adhesive over firm, flat, clean, smooth, hard surfaces [free of cracks and foreign substances], of wood, concrete, vinyl, or terrazzo) of the product against abrasive wear properly installed and maintained installation for a period of Five (5) Years. Failure is defined as the loss due to abrasive wear of Fifteen (15%) percent of the pile thickness in any given area. This warranty is for abrasive wear only, and does not cover burns, cuts, gouges, pilling, matting of pile, shedding, flattening of the pile or pattern, staining, soiling, oiling, fading, or fiber loss due to abnormal usage. No warranty is extended for use of the product on stairs or for product which has been taken up from the location where it was originally installed and was reinstalled. If a warranty claim due to abrasive wear of glued down product is established to JCH International's satisfaction, JCH International agrees, at its option, to repair or to replace the product out of current lines at the time of replacement: First Year- 100%, Second year- 75%, Third Year- 50%, Fourth year- 25%, Fifth year- 15% of the replacement cost of the product. An extended warranty is not offered. The products should be maintained by frequent vacuum cleaning, as needed. Wet or damp products should not be vacuumed. Spots or spills should be cleaned within 6 hours, and the product should be cleaned by carpet shampooing methods, household detergent and water, or steam-cleaning methods. Proof of installation date must be filed with JCH International, or its representative, as stipulated below.

Limitations of Warranty

In the event of a warranty claim established to JCH International's satisfaction, JCH International agrees, at its option to repair, or to replace the product out of current lines at the time of replacement. The labor cost of receiving and/or re-installing replacement materials are to be born by the purchaser. No liability will be assumed for any consequential damage, loss, or expense. No liability will be assumed for commercial shade variations or for materials with visible defects after such materials have been installed. This warranty is in lieu of any other express guarantees, warranties, liabilities, or obligation on the part of JCH International. Implied guarantees or warranties of merchantability, or fitness for a particular purpose, are listed in duration to the terms of the applicable express warranty set forth above. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state. To process any claim under this warranty, submit a 12"x12" initial sample of the failed product for laboratory evaluation together with a copy of the original dealer invoice and proof of installation date registration to the dealer from whom this carpet was purchased. Or, in extenuating circumstances, contact JCH International, 978 Hermitage Road NE, Rome GA 30161, 800-328-9203, 706-295-4111.